

No

25512UFR050

Version 1

1	Unique identification Code of the product type	Monarperm TP 140R
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 1.7.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Sarking and underlays for roofing
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Monarperm TP 140R Monarflex s.r.o. Továrenská 1 943 03 Štúrovo Slovak Republic
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3
7	In case of the declaration of performance concerning a construction product covered by a harmonised standard The notified testing laboratory Bodycompany No. has carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product () () ()	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	F Pass	EN 13859-1:2010
resistance to water penetration	W1 Pass	
Tensile strength longitudinal	≥ 400 N/50 mm	
Tensile strength transverse	≥ 350 N/50 mm	
Elongation longitudinal	≥ 30 %	
Elongation transverse	≥ 25 %	
resistance to tearing longitudinal	≥ 180 N	
resistance to tearing transverse	≥ 170 N	
artificial aging behaviour: resistance to water penetration	W1 Pass	
artificial aging behaviour: tensile strength longitudinal	≥ 400 N/50 mm	
artificial aging behaviour: tensile strength transverse	≥ 320 N/50 mm	
artificial aging behaviour: elongation longitudinal	≥ 27 %	
artificial aging behaviour: elongation transverse	≥ 25 %	
flexibility at low temperatures (pliability)	Pass -25 °C	
Dangerous substances	See Note	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Štúrovo

25.10.2013

dd/mm/yyyy



Miroslav PETRECH
General Manager