

No

26182UFR058

Version 1

1	<p>Unique identification Code of the product type</p>	<p>Monarperm TP Ultra</p>
2	<p>Identification of the construction product, in accordance with article 11(4)</p>	<p>Lot-Number. see packaging of product valid from 3.6.2014</p>
3	<p>Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer</p>	<p>Sarking and underlays for roofing</p>
4	<p>Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)</p>	<p>Monarperm TP Ultra Monarflex s.r.o. Továrenská 1 943 03 Štúrovo Slovak Republic</p>
5	<p>Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)</p>	<p>not applicable</p>
6	<p>System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V</p>	<p>System 3</p>
7	<p>In case of the declaration of performance concerning a construction product covered by a harmonised standard</p> <p>The notified testing laboratory Bodycompany No. 1301 Technický a skúšobný ústav stavebný,n.o. has carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product ()</p> <p>()</p> <p>()</p>	
8	<p>In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued</p>	<p>not applicable</p>

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 13859-1:2010
Resistance to water penetration	W1 Pass	
Tensile strength longitudinal	400(+30) N/50 mm	
Tensile strength transverse	450(+30) N/50 mm	
Elongation longitudinal	60(+15) %	
Elongation transverse	75(+15) %	
Resistance to tearing longitudinal	350(-+30) N	
Resistance to tearing transverse	400(-+30) N	
Artificial aging behaviour: resistance to water penetration	W1 Pass	
Artificial aging behaviour: tensile strength longitudinal	360(+30) N/50 mm	
Artificial aging behaviour: tensile strength transverse	400(+30) N/50 mm	
Artificial aging behaviour: elongation longitudinal	50(+15) %	
Artificial aging behaviour: elongation transverse	60(+15) %	
Flexibility at low temperatures (pliability)	Pass -40 °C	
Dangerous substances	See note	

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Štúrovo

3.6.2014 13:07:25

dd/mm/yyyy

Miroslav PETRECH
General Manager