

No

14128VCL029

Version 1

1	Unique identification Code of the product type	Reflex 275
2	Identification of the construction product, in accordance with article 11(4)	Lot-Number. see packaging of product valid from 1.7.2013
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Flexible sheets for waterproofing - Plastic and rubber vapour control layers
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Reflex 275 Monarflex s.r.o. Továrenská 1 943 03 Štúrovo Slovak Republic
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	not applicable
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3
7	<p>In case of the declaration of performance concerning a construction product covered by a harmonised standard</p> <p>The notified testing laboratory Bodycompany No. TBU KIWA DAP-PL-4346.00 has carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product ()</p> <p>()</p> <p>()</p>	
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	not applicable

9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Watertightness	Pass	EN 13984:2013
Tensile strength longitudinal	≥ 450 N/50 mm	
Tensile strength transverse	≥ 380 N/50 mm	
Elongation longitudinal	≥ 15 %	
Elongation transverse	≥ 10 %	
resistance to impact method A	≤ 200 mm	
resistance to impact method B	NPD	
resistance to tearing	≥ 300 N	
water vapour resistance	sd min.1500 m	
shear resistance of joints	≥ 50 N	
durability: water vapour resistance after artificial ageing	Pass	
durability: water vapour resistance after chemicals exposure	Pass	
Dangerous substances	See Note	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not applicable

10

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Štúrovo

20.6.2013

dd/mm/yyyy



Miroslav PETRECH
General Manager